





MV-25

2-pc Ball Valve

- Investment casting for body and cap
- Full bore
- Threaded ends: ANSI B2.1, BS 21, DIN 259/2999
- Pressure rating : 1000 PSI (PN63)
- Working temperature: -25°C +180°C
- Material: CF8M, CF8, CF3M, WCB



DIMENSION LIST

SIZE	d	L	H	W	N • m	Kgs
1/4"	11.5	49	54	100	4	0.23
3/8"	12.5	49	54	100	4	0.23
1/2"	15	57	56	100	5	0.24
3/4"	20	64	65	115	8	0.45
1"	25	77	70	150	10	0.65
1-1/4"	32	90	75	150	14	1.05
1-1/2"	40	105	93	180	18	1.70
2"	50	125	99	180	25	2.61
2-1/2"	65	154	123	245	48	5.01
3"	76	173	140	245	75	7.61
4"	94	221	175	278	110	14.75

MATERIAL LIST

ITEM	PART	MATERIAL	QTY
1	Body	CF8M	1
2	Ball Seat	R-PTFE15%	2
3	Ball	SS316	1
4	Body Gasket	PTFE	1
5	Cap	CF8M	1
6	Stem	SS316	1
7	Thrust Washer	PTFE	1
8	Stem Packing	PTFE	1
9	Gland Nut	SS304	1
10	Handle	SS304	1
11	Spring Washer	SS304	1
12	Nut	SS304	1
13	Lock Device	SS304	1
14	Handle Cover	Plastic	1